



China 608rs Bearing Supplier

NTN Deep groove ball bearing 6912LLU



6912LLU Bearing 2D drawings and 3D CAD models

Bearing No. 6912LLU

Size	60x85x13 mm
Bore Diameter	60 mm
Outer Diameter	85 mm
Width	13 mm
d	60 mm
D	85 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	65 mm
da max	66,5 mm
Da max.	80 mm
ra max.	1 mm
Weight	0,193 Kg
Basic dynamic load rating (C)	16,4 kN
Basic static load rating (C0)	14,3 kN
Reference speed	4 300 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359587791
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0



China 608rs Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	60MM Bore; 85MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.425
Outside Diameter	3.346 Inch 85 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	2.362 Inch 60 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
bore diameter:	60 mm
precision rating:	ISO Class 0



China 608rs Bearing Supplier

outside diameter:	85 mm
finish/coating:	Uncoated
overall width:	13 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	13 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	13 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	4300 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	8900 RPM
dynamic load capacity:	16400 N
series:	69
static load capacity:	14300 N
manufacturer product page:	Click here